

CLOUD 9 CAVIAR & CRYSTAL 9MM

- MADE WITH YOU IN MIND
- CLOUD 9 APT
- SUITABLE FOR HIGH WEAR AREAS
- EXCELLENT FOR IMPACT SOUND REDUCTION
- EXCELLENT THERMAL INSULATION PROPERTIES

RECOMMENDED AREAS OF USE

DOMESTIC - CONTRACT WEAR RATING. SUITABLE FOR LUXURY AREAS SUCH AS LIVING ROOMS, STAIRS AND BEDROOMS.



Manufactured in the UK & BS EN 14499:2015

STANDARD SPECIFICATIONS		
TOP SURFACE	Printed stitch bonded white crepe paper	
BOTTOM SURFACE	Spun bonded non-woven fabricc	
NOMINAL THICKNESS	9.00 mm	
NOMINAL ROLL WEIGHT	23.9 kg	52.7 lb
WEIGHT PER UNIT AREA	1586 g/m²	47 oz/yd²
ROLL LENGTH	11.0 m	36.0 ft
ROLL WIDTH	1.37 m	54 in
GUARANTEE	Lifetime of the initial carpet installation (when used in recommended areas)	
CORE DENSITY	160 kg/m³	
PRODUCT DENSITY	176 kg/m³	

BS EN 14499:2015 TEST RESULTS - UK and EU STANDARD for CARPET UNDERLAYS				
END USE CLASSIFICATION	BS EN 14499	HC/U		
WORK OF COMPRESSION AFTER 1000 IMPACTS	BS 4098	>130 J/m ²		
RETENTION OF WORK OF COMPRESSION	BS 4098	>90 %		
LOSS IN THICKNESS AFTER STATIC LOADING	BS 4939 ISO 3416	<5.00 %		
LOSS IN THICKNESS AFTER DYNAMIC LOADING	BS ISO 2094 (R05)	<5.00 %		
RESISTANCE TO CRACKING	BS EN 14499	Pass		

INDOOR AIR QUALITY TEST				
TESTED TO ISO16000				
EUROFINS INDOOR AIR COMFORT ® STANDARD		Pass	ÉMISSIONS DANS L'AIR INTÉRIEUR	
EUROFINS INDOOR AIR COMFORT GOLD ® STANDARD		Pass	$\Delta +$	
FRENCH VOC REGULATIONS		A+		
FRENCH CMR COMPONENTS		Pass	Tritomation sur le nomes d'étrissions de substances condines dans l'air collensus, présentest un risque de l'accordin per inhabition, sur une étriteire de classe allant de A1 chies facture describus qu'Efficie de missionique.	
ITALIAN CAM		Pass		
AgBB/ABG		Pass		
FORMALDEHYDE EMISSION CLASS		E1		
BREEAM INTERNATIONAL		Compliant		
LEED v4 (Outside U.S.)		Compliant		
BREEAM ® NOR		Compliant		

OTHER RELEVANT TESTS		
THERMAL RESISTANCE (TOG RATING)	BS 4745	2.3 TOG
IMPACT SOUND IMPROVEMENT INDEX (Test/Rated)	BS EN ISO 10140-3 BS EN ISO 717-2)	39 dB



ISSUE 3 23 NOV - 20